

F/UTP-CAT6

QS Code:6FO-008545

4x2x23AWG
F/UTP-CAT6 Lan Cable

PE Insulation/PE Jacket

Product Code CAT6.F/UTP.4P.23.E.BK.23070624

Application

- 100Base-T4
- 100Base-TX
- 1000Base-T
- 1000Base-TX
- 155Mbps ATM
- 622Mbps ATM

Reference Standard

- ANSI/TIA-568.2-D

Packing

- 100m/Box

Product structure

Conductor	0.56 ± 0.01mm (23AWG)	
Insulation	PE	
Insulation DiameterØ	1.1 ± 0.1mm	
Insulation Colour	Blue/White-Blue	Orange/White-Orange
	Green/White-Green	Brown/White-Brown
Separator	Yes	
Wrap Tape	100% Coverage	
Drain Wire	0.4 ± 0.01TC	
AL-Mylar	100% Coverage	
Rip cord	Yes	
Jacket	PE	
Jacket DiameterØ	7.4 ± 0.3mm	
Thickness	0.55 ± 0.1mm	
Jacket Colour	BK	


Electrical properties @ 20℃

Working capacity	≤5.6nF/100m(@1kHz)
Capacitive unbalance to earth	≤160pF/100m
Delay skew	≤45ns/100m
conductor resistance	≤93.8 Ω/km
Electric balance of the conductor	≤5%(@20℃)
insulation resistance	≥5000M Ω.km
Impedance: 1-250MHz	100 ± 22 Ω

Mechanical properties

Operating temperature	— 20~75℃
Minimum bending radius	8 × Cable OD
Jacket Elongation at break	≥350%
Jacket Tensile strength	≥9Mpa
Jacket Aging conditions	100℃ 48h
Jacket Elongation at break After Aging	≥75% Before Aging
Jacket Tensile Strength After Aging	≥75% Before Aging
Low temperature winding experiment	-20℃ 4h No visible cracks

Date	Version	ECR	Drawn	Approved
2023/7/7	A/0			



F/UTP-CAT6

QS Code:6FO-008545

4x2x23AWG F/UTP-CAT6 Lan Cable

PE Insulation/PE Jacket

Product Code CAT6.F/UTP.4P.23.E.BK.23070624

High Frequency Electrical performance:(20℃ 100m)

Frequency (MHz)	ATT (≤dB)	NEXT (≥dB)	PSNEXT (≥dB)	ELFEXT (≥dB)	PS ELFEXT (≥dB)	RL (≥dB)	Spread out 100m cable and test it
1.00	3.0	65.0	62.0	63.3	60.3	19.0	
4.00	4.0	63.0	60.5	51.2	48.2	19.0	
8.00	5.7	58.2	55.6	45.2	42.2	19.0	
10.00	6.3	56.6	54.0	43.3	40.3	19.0	
16.00	8.0	53.2	50.6	39.2	36.2	18.0	
20.00	9.0	51.6	49.0	37.2	34.2	17.5	
25.00	10.1	50.0	47.3	35.3	32.3	17.0	
31.25	11.4	48.4	45.7	33.4	30.4	16.5	
62.50	16.5	43.4	40.6	27.3	24.3	14.0	
100.00	21.3	39.9	37.1	23.3	20.3	12.0	
200.00	31.5	34.8	31.9	17.2	14.2	9.0	
250.00	35.9	33.1	30.2	15.3	12.3	8.0	

Date	Version	ECR	Drawn	Approved
2023/7/7	A/0			

Kenable Limited

Sandwash Close, Rainford Industrial Estate, St Helens, WA11 8LY, United Kingdom